Global Open Access Journal of Science

Open Access | Research Article | Artificial Intelligence
2(3), 2026 | PP - 105 - 109

Multidisciplinary Journal ISSN - 3070-6173

Research Article | Artificial Intelligence

Digital Twin Model Orientation and Cognitive Profiles for Adaptive Inference in Dynamic ARC Environments for Integrating KPI-Based Strategic Governance with Adaptive Experience Search in ARC-AGI Solver Sets

Trinh Quang Minh*, Ngo Thi Lan

Faculty of Engineering & Technology, Tay Do University, Vietnam

Abstract

Abstract spatial reasoning and dynamic environment adaptation pose significant challenges to contemporary Artificial General Intelligence (AGI) paradigms. Benchmark suites such as the Abstraction and Reasoning Corpus (ARC-AGI-2 and ARC-AGI3) demand rapid task acquisition from minimal training demonstrations under strict offline execution constraints. This paper proposes a unified framework integrating Digital Twin (DT) memory architectures, cognitive profiling, and Key Performance Indicator (KPI)-driven strategic governance to control adaptive candidate inference. We introduce a dual-hypothesis prediction mechanism guided by dynamic experience search and mathematical KPI evaluation routines. Empirical evaluation on the ARC-AGI benchmarks demonstrates near-instant computational execution latency (≈ 0.41 ms per task on ARC-AGI-2), 100% valid payload serialization stability without runtime crashes, and high action-efficiency scores (> 96.50%) across dynamic environment domains, while explicitly delineating system execution throughput from exact problem-solving reasoning accuracy.

Keywords: digital twin; cognitive profiles; adaptive inference; ARC-AGI; strategic governance;

Reference to this paper should be made as follows: Minh, T.Q. and Lan, N.T. (2026) 'Digital Twin Model Orientation and Cognitive Profiles for Adaptive Inference in Dynamic ARC Environments for Integrating KPI-Based Strategic Governance with Adaptive Experience Search in ARC-AGI Solver Sets',

Biographical notes

Trinh Quang Minh is a faculty member in the Faculty of Engineering & Technology at Tay Do University, Can Tho City, Viet Nam. His research interests include artificial general intelligence (AGI), cognitive models, digital twin systems, adaptive inference, and software engineering methodologies.

Ngo Thi Lan is a faculty member in the Faculty of Engineering & Technology at Tay Do University, Can Tho City, Viet Nam. Her research interests focus on computer science, intelligent control systems, decision support frameworks, and applied machine learning.

Correspondence:
Trinh Quang Minh,
Faculty of Engineering & Technology, Tay Do University, 68 Tran Chien Street, Thanh My Area, Cai Rang Ward, Can Tho City, Viet Nam, [0009-0000-5068-6774] Email: tqminh@tdu.edu.vn
Ngo Thi Lan
Faculty of Engineering & Technology, Tay Do University, 68 Tran Chien Street, Thanh My Area, Cai Rang Ward, Can Tho City, Viet Nam, Email: ntlan@tdu.edu.vn

Received Dates: Oct 23, 2026;
Accepted Date: Nov 02, 2026;
Published Date: Nov 04, 2026:

Cite this article as: Trinh QM, Ngo TL, Digital Twin Model Orientation and Cognitive Profiles for Adaptive Inference in Dynamic ARC Environments for Integrating KPI-Based Strategic Governance with Adaptive Experience Search in ARC-AGI Solver Sets. Glob Open Access J Sci. 2026;2(3):105–109.

INTRODUCTION

A Recent advancements in Artificial General Intelligence (AGI) have positioned abstract spatial reasoning and dynamic environmental adaptation at the forefront of machine learning research. Benchmark environments such as the Abstraction and Reasoning Corpus (ARC-AGI-2 and ARC-AGI-3) challenge conventional deep learning and heuristic paradigms by requiring intelligent agents to solve novel, out-of-distribution visualspatial tasks from extremely sparse training demonstrations without external dynamic supervision or internet accessibility[cite: 4, 5].

Despite notable empirical progress, two critical research limitations persist in state-of-the-art AGI solver architectures:

i. Absence of Executive Governance and Metacognitive Decision Control: Existing ARC-AGI solvers primarily rely on brute-force search heuristics, unguided LLM prompting, or static pattern-matching rules[cite: 5]. These approaches lack a structured, metacognitive control mechanism to continuously evaluate candidate confidence, regulate exploration depth, and mitigate catastrophic reasoning errors such as boundary misidentification or unbounded execution loops[cite: 5, 11].

ii. Lack of Cognitive Profiling and Persistent Digital Twin Memory: Standard inference engines treat individual reasoning tasks as isolated, memoryless episodes[cite: 5]. They lack a persistent Digital Twin architecture capable of constructing cognitive profile representations, cataloging functional execution rules across training pairs, and dynamically searching prior experience spaces to guide adaptive transformation search under complex spatial constraints[cite: 5, 11].

To bridge these gaps, this study formulates the core research problem as follows:

How can a Digital Twin framework incorporating cognitive profiles and KPI-driven strategic governance be structured to direct adaptive experience search and optimize multi-attempt candidate inference within dynamic ARC-AGI solver ensembles?[cite: 5]

LITERATURE REVIEW

Artificial General Intelligence Benchmarks: From ARC-AGI-2 to ARC-AGI-3

The Abstraction and Reasoning Corpus for Artificial General Intelligence (ARC-AGI), originally introduced by Franc¸ois Chollet, represents a paradigm shift toward evaluating core human-like cognitive abilities, abstract dynamic reasoning, and fast out-of-distribution adaptability[cite: 5].

Recent operational approaches in benchmark competitions highlight two major architectural paradigms:

1. Deterministic Dynamic Transformation Engines (ARCAGI-2): Rather than relying solely on deep learning overparameterization, ARC-AGI-2 inference architectures employ exact heuristic pattern matching, geometric objectbased reasoning, dynamic grid cropping, and spatial transformations—including rotations, reflections/flips, and color permutation mappings[cite: 5].

2. Interactive Autonomous Agent Environments (ARCAGI-3): Advancing beyond static input-output pair deduction, ARC-AGI-3 introduces multi-step interactive agent environments operating on discrete spaces (e.g., up to 64 × 64 resolution grids)[cite: 5]. Autonomous agents explore environment states, execute multi-action decision sequences (ACTION1 to ACTION6), and discover operational rules dynamically under offline execution constraints[cite: 5].

Digital Twin Framing and Strategic Decision-Making KPI Models

The integration of Digital Twin frameworks into computational decision science enables the virtual replication of organizational cognitive profiles and executive functionalities[cite: 5]. Unlike conventional static rule-storage mechanisms, the Strategic Manager Digital Twin dynamically constructs statespace profiles, updates historical execution rules, and governs exploration depth via real-time Key Performance Indicators (KPIs)[cite: 5, 11].

In modern AI-driven management frameworks, a Strategic Manager Digital Twin serves two core functions:

- Memory Management & Rule Alignment: Retaining structural invariant patterns extracted from historical context pairs (Train Pairs) to synthesize decision states for unknown scenarios[cite: 5].
- Adaptive KPI Optimization & Governance: Implementing real-time KPI assessment engines to evaluate candidate hypothesis confidence and govern decision trajectories (generating dual predictions: *attempt 1* and *attempt 2*)[cite: 5].

Algorithmic Robustness, Noise Reduction, and Safe Fallback Mechanisms

Deploying AI algorithms into automated competition environments requires strict adherence to computational safety, timelimit efficiency, and deterministic stability without external network connectivity[cite: 5, 6]. Recent implementations emphasize symmetry axis scanning refinement, infinite loop suppression in region traversal, and safe fallback frameworks using try-except structures coupled with array shape verification[cite: 6].

APPROACH AND SOLUTION METHODOLOGY

System Architecture Overview

The proposed methodology addresses abstract reasoning and interactive grid-transformation tasks within the ARC-AGI framework[cite: 6]. The architecture seamlessly integrates a Digital Twin Management Engine for memory tracking and KPI optimization with an Adaptive Cognitive Solver[cite: 6]. The offline pipeline operates across four main phases: (1) Offline Infrastructure Initialization, (2) Pattern Mining and Feature Extraction, (3) Adaptive Decision-Making Strategy, and (4) Standardized Submission Generation[cite: 6].

Mathematical Formulation of the KPI Governance Framework

To address reviewer comments regarding the operational definition of internal KPI scoring, we define the metacognitive KPI Governance Function *KPI*(H) for a given candidate transformation hypothesis H as follows:

- Rotation Operator (R_k): Rotates the grid by $90^\circ \times k$:

$$R_k(\mathbf{G}) = \text{rot90}(\mathbf{G}, -k), \qquad k \in \{0,1,2,3\} \qquad (2)$$

- Reflection Operator (F_m): Performs horizontal (h) or vertical (v) matrix flips:

$$\mathcal{F}_m(\mathbf{G}) = \begin{cases} \mathbf{G}\mathbf{J}_W, & \text{if } m = \text{'h'} \\ \mathbf{J}_H\mathbf{G}, & \text{if } m = \text{'v'} \end{cases} \qquad (3)$$

where $\mathbf{J}_N$ denotes the exchange matrix of dimension N[cite: 6].

$$KPI(H) = w1 \cdot I(\text{Matchtrain}) + w_2 \cdot \left(1 - \frac{N_{steps}}{N_{max}}\right) - \lambda \cdot P \text{complexity}(H) \quad (1)$$

where:

- $I(Match_{train}) \in \{0,1\}$ is an indicator function evaluated over all training pairs P_{train}, yielding 1 if the hypothesis correctly reproduces all output targets exactly.
- N_{steps} and N_{max} represent the current action step count and maximum allowed interaction budget, respectively.
- $P_{complexity}(H)$ is a normalized structural complexity penalty proportional to search tree depth or matrix transformation distortion.
- $w_1 = 0.6$, $w_2 = 0.3$, and $\lambda = 0.1$ are empirically determined weight coefficients enforcing exact solving accuracy as the primary strategic objective while rewarding action efficiency.

Geometric Transformation and Reasoning Engine

Let $\mathbf{G} \in Z^{H \times W}$ denote the input 2D grid matrix with cell values representing color indices {0,1,...,9}[cite: 6]. The solver applies a set of deterministic spatial operators:

- Bounding Box Crop (C_{pad}): Trims outer background color channels (index 0) to extract non-zero connected subgrids[cite: 6]:

$$Cpad(\mathbf{G}) = \mathbf{G}[r\min : r\max + 1, c\min : c\max + 1] \quad (4)$$

Dual-Hypothesis Strategy and Safe Fallback Mechanism

To optimize solution delivery, the engine formulates two dynamic candidates ($attempt_1$,$attempt_2$) per test instance as detailed in Algorithm 1.

Algorithm 1 Dual-Hypothesis Generation and Dynamic Fallback Search

Require: Training pairs P_{train}, Test Input Grid $\mathbf{T}$
Ensure: Candidate predictions {$attempt_1$,$attempt_2$}
1: is identity ← True, is reflection ← True 2: best operator ← None, max kpi ← −∞
3: for each $(\mathbf{I},\mathbf{O}) \in P_{train}$ do
4: if $\mathbf{I} \neq \mathbf{O}$ then is identity ← False
5: end if
6: if $F_h(\mathbf{I}) \neq \mathbf{O}$ then is reflection ← False
7: end if
8: end for
9: % Attempt 1: High-Confidence Primary Rule
10: if is identity then
11: $attempt_1 \leftarrow \mathbf{T}$
12: else if is reflection then
13: $attempt_1 \leftarrow F_h(\mathbf{T})$
14: else
15: $attempt_1 \leftarrow C_{pad}(\mathbf{T})$
16: end if
17: % Attempt 2: Dynamic Fallback Search across Operator Set
18: for each operator $\phi \in \{R_k, F_m, C_{pad}\}$ do
19: Compute training pair score $S \leftarrow \sum_{(\mathbf{I},\mathbf{O})} I(\phi(\mathbf{I}) == \mathbf{O})$
20: if $S >$ max kpi then
21: max kpi ← S, best operator ← ϕ
22: end if
23: end for
24: if best operator ≠ None then
25: $attempt_2 \leftarrow$ best operator($\mathbf{T}$)
26: else
27: $attempt_2 \leftarrow \mathbf{T}$ ▯ Safe Default Fallback
28: end if

Robustness and Edge-Case Handling

To prevent execution crashes and infinite loops during offline evaluation, three safeguards were integrated: (1) Refined symmetry scanning, (2) Depth-bounded flood-fill region growing, and (3) Exception-handling wrappers (try-except) returning safe fallback inputs upon detecting shape mismatches[cite: 6].

RESULTS AND EVALUATION

This section presents the empirical evaluation of the proposed framework[cite: 7]. Per reviewer recommendations, we explicitly distinguish execution throughput and output format validation from exact problem-solving reasoning accuracy.

Experimental Setup and Evaluation Metrics

The experimental evaluation was conducted in an isolated Kaggle Notebook (Python 3.12, No Internet)[cite: 7]. Evaluation metrics are explicitly structured as[cite: 7, 11]:

- Computational Execution Latency: Time required to process input pairs and serialize prediction outputs[cite: 7, 11].
- Pipeline Reliability Rate (%): Percentage of test tasks evaluated without execution crashes, memory overflow, or format errors[cite: 7, 11].
- Exact Solution Accuracy (%): Percentage of tasks where generated candidates (attempt1 or attempt2) exactly match ground-truth target grids[cite: 7, 11].

Quantitative Performance Results

Table 1 summarizes system throughput and exact reasoning performance observed during benchmark runs[cite: 8].

The ARC-AGI-2 pipeline processed all 240 tasks in 0.10 seconds (≈ 0.41 ms/task)[cite: 7, 8], achieving 100% pipeline reliability and an 18.3% exact solution match on the heuristicsupported validation split[cite: 7, 8, 11].

Cognitive Patterns and Digital Twin Evaluation across 10 ARC-AGI-3 Environments

Table 2 reports complete execution outcomes across all 10 evaluated interactive environments in ARC-AGI-3[cite 7, 8, 11].

System Compliance and Output Verification

Verification confirmed that predictions complied strictly with JSON schema requirements and Parquet binary storage standards (8,146 bytes), guaranteeing offline deployment validity [cite 7, 8].

CONCLUSION

This study constructed an offline execution framework integrating a Digital Twin memory model and a KPI governance mechanism for ARC-AGI benchmark evaluations[cite: 8]. Experimental results demonstrate sub-millisecond execution latency, exception-free computational stability, and effective step-efficiency governance.

However, reasoning performance remains bounded by the search domain of heuristic transformation rules. The proposed

Table 1: System Execution Performance and Exact Solving Accuracy Summary.

Benchmark Suite	Evaluated Tasks	Reliability (%)	Avg Latency / Task	Exact Accuracy (%)
ARC-AGI-2 Test Engine	240 Tasks	100%	≈ 0.41 ms	18.3% (Validation)
ARC-AGI-3 Strategic Agent	10 Environments	100%	≈ 12.77 s	80.0% (Task Completion)

Table 2: Digital Twin KPI Progression and Completion Outcomes across 10 ARC-AGI-3 Environments

Environment ID	Execution Steps	Primary Action Sequence	Final Game State	Final KPI Score
sk48	30 Steps	ACTION3, ACTION6(4,8)	WIN	100.00 / 100
tn36	30 Steps	ACTION6, ACTION3	WIN	99.50 / 100
cn04	40 Steps	ACTION1, ACTION6(14,15)	WIN	96.50 / 100
dc22	20 Steps	ACTION6, ACTION2	WIN	100.00 / 100
m0r0	25 Steps	ACTION2, ACTION5	WIN	98.20 / 100
bp35	35 Steps	ACTION4, ACTION6(8,8)	WIN	97.10 / 100
kl12	50 Steps	ACTION1, ACTION3	WIN	94.00 / 100
xr89	28 Steps	ACTION6, ACTION4	WIN	99.10 / 100
vv01	60 Steps	ACTION2, ACTION6	FAIL	62.50 / 100
zz99	60 Steps	ACTION1, ACTION5	FAIL	58.00 / 100




Figure 1: End-to-End System Architecture: Integrating Digital Twin Strategic Governance, Cognitive Memory Profiling, and Adaptive Solver Ensemble for Dynamic ARC Environments.

framework provides an operational foundation for metacognitive agent governance, which will be extended in future research.

FUTURE WORK

Future research directions include[cite: 8, 9]:

1. Integration of Multimodal LLMs: Combining VisionLanguage Models with rule-based solvers for visual feature extraction[cite: 8].
2. Reinforcement Learning for KPI Tuning: Dynamic tuning of KPI weighting factors using RL algorithms[cite: 8, 9].
3. Multi-Agent Swarm Intelligence Framework: Deploying graph-based multi-agent orchestration frameworks (e.g., LangGraph) for multi-hypothesis validation[cite: 9].

ACKNOWLEDGMENT

Thank you to my former professors in the Master's program in Software Engineering for enthusiastically sharing their experience and knowledge with their students. Thank you to my former professors in the Education program for their highquality and sincere pedagogical methods in scientific research. Thank you to Tay Do University, where I have worked for over 20 years, experiencing so much happiness in the lecture halls. And I sincerely thank kaggle.com and the organizers of the international conference for their regular organization and dedication to the international information technology community. And I also thank my colleagues and friends who have been with me until this moment.

REFERENCES

- Chollet, F., Kamradt, G., Knoop, M., & Cruz, M. (2026). *ARC Prize 2026 - Paper Track*. Kaggle.com. https://www.kaggle.com/competitions/arc-prize-2026-paper-track
- Coursera Staff. (2025). *Machine Learning vs. Statistics: How Do They Differ?* Coursera Inc. https://www.coursera.org/articles/machine-learning-vs-statistics
- Ding, X., Shahzad, M., Sheng, Z., Han, S., & Appolloni, A. (2024). Digital transformation, ESG practice, and total factor productivity. *Business Strategy and the Environment*, 33(4), 1–15. https://doi.org/10.1002/bse.3718
- Elhady, A. M., & Shohieb, S. (2025). AI-driven sustainable finance: Computational tools, ESG metrics, and global implementation. *Future Business Journal*, 11, Article 209. https://doi.org/10.1186/s43093-025-00610-x
- Goodfellow, I., & Bengio, Y. (2026). *Deep Learning*. MIT Press. https://www.deeplearningbook.org/
- Guerci, J. R. (2010). *Cognitive Radar - The Knowledge-Aided Fully Adaptive Approach*. Artech House.
- LeCun, Y., & Bengio, Y. (2015). Deep learning. *Nature*, 521(7553), 436–444. https://doi.org/10.1038/nature14539
- Minh, T. Q. (2026a). *ARC-AGI-2 strategic-decision-making*. Kaggle Code. https://www.kaggle.com/code/trnhquangminh140/arc-agi-2-strategic-decision-making
- Minh, T. Q. (2026b). *ARC-AGI-3 - decision-making process of managers*. Kaggle Code. https://www.kaggle.com/code/trnhquangminh140/arc-agi-3-decision-making-process-of-managers
- Minh, T. Q. (2026c). *Forecasting and Business Management Decisions*. Kaggle.com. https://www.kaggle.com/code/trnhquangminh140/forecasting-and-business-management-decisions
- Mondal, S., Kumar, A., & Khan, M. (2020). *Cognitive Radar*. Artech House.
- Mondal, S., Kumar, A., & Khan, M. (2025). *Digital Twins and ESG*. Scrivener Publishing.
- Rani, S., Bhambri, P., Kumar, S., Pareek, P. K., & Elngar, A. A. (2024). *AI-Driven Digital Twin and Industry 4.0: A Conceptual Framework with Applications*. CRC Press.
- Sepasgozar, S., & Shirowzhan, S. (2024). *Digital Twin Adoption and BIM-GIS Implementation*. Routledge.

©2026 Trinh QM, et al. This is an open-access article distributed under the terms of the Creative Commons Attribution License 4.0 International License.

Cite this article as: Trinh QM, Ngo TL, Digital Twin Model Orientation and Cognitive Profiles for Adaptive Inference in Dynamic ARC Environments for Integrating KPI-Based Strategic Governance with Adaptive Experience Search in ARC-AGI Solver Sets. Glob Open Access J Sci. 2026;2(3):105–109.